



GLOSS METERS

Gloss Meter - Make Color Matching a Pleasure

Comprehensive color measurement and management solutions are crucial for applications such as color matching, quality control, and research. They are essential for maintaining product quality, ensuring consumer satisfaction, and facilitating research and development in various industries.

- Supported devices: YS series spectrophotometer
- Operating system: This software is compatible with Win7/Win10/Mac/Linux Unix systems.
- Supported languages: English.
- Supporting color sample input and saving
- Color detection and quality management
- Automated color matching
- Formulation correction
- K&S color adjustment

Gloss Meter - Make Color Matching a Pleasure

Feature of Gloss Meter

Gloss Meter STABLE PERFORMANCE HIGH PRECISION

The intelligent touch screen gloss meter series and the economic gloss meter series, developed with exclusive intellectual property rights, adhere to international standard ISO 2813. These devices represent the world's first full-scale touch screen gloss meters. Offering both tri-angle and 60-degree models to meet a variety of customer needs, they become even more user-friendly when combined with PC software. Their stable performance and impressive measurement accuracy have

earned them global acclaim.

- Color capacitive touch screen, the world' s first full touch operation
- Simultaneous display multiple sets of measurement data, good for comparison
- Manually input gloss value, convenient to use
- PC software have powerful extended functions

APPLICATIONS

- A 3.5-inch high-resolution touch screen with a display size of 480 x 320 pixels.
- Compliant with ASTM D523, ASTM D2457and ISO 2813 standards.
- Attractive design with an intuitive man-machine communication interface.
- Single-button operation for measuring all angles at the same location.
- Capable of displaying up to five sets of measurement data, facilitating easy comparisons.
- Supports basic measurement, statistical measurement, and continuous measurement to meet diverse requirements.
- Equipped with a built-in, long-lasting Li-ion rechargeable battery.
- Offers extended functionality by connecting to a PC.
- Allows manual input of gloss values for convenient use.
- Features ample storage capacity to save over 5000 sets of data.

Gloss meter

Leather Sample

Leather Sample

Hardware Parts

Hardware Parts

Marble Sample

Marble Sample

Plastic Sample

Plastic Sample

Product Show

Large Touch Screen

Large Touch Screen

Tri-angle for Different Use

Tri-angle for Different Use

Multi sets of Data for Better Comparison

Multi sets of Data for Better Comparison

GQC6 PC Software

GQC6 PC Software

FEATURES

- **Multi-angle:** Three measuring angles (20 degrees, 60 degrees, and 85 degrees) that can be measured simultaneously.
- **Advanced configuration:** Incorporating high-end hardware with a range of innovative technologies.
- **Ample capacity:** Supports 1000 basic modes, 5000 statistical modes, and 5000 continuous modes.
- **User-friendly:** Allows manual entry of gloss standard data for customer convenience.

Advantages

- One-click color matching, completing a day's worth of color matching work in just one hour.
- Exceptional color matching efficiency, leading to substantial savings in labor, materials, and time costs.
- Our in-house developed calculation engine enhances the precision of calculation formulas.
- Various formulas to enhance the utilization of inventory pigments.
- Rapid and precise color correction technology that minimizes metamerism issues.
- An expert-level formula system to guarantee that the formulations meet the specified requirements.

TECHNICAL SPECIFICATIONS

Model	TT-TRI-GLOSS-III	TT-TRI-GLOSS-NHG60	TT-TRI-GLOSS-NHG60M
Optical Geometry	20° / 60° / 85°	60°	60°

Standards compliant	ASTM D 523, ISO 2813		
Facula (inches)	20°:0.933x0.39 60°:0.35x0.59 85°:0.2x1.42	0.35x0.59	0.08x0.12
Measuring range	20°:0~2000GU 60°:0~1000GU 85°:0~160GU	0~1000GU	0~1000GU
Precision value	0.1GU		
Repeatability	0~200GU:±0.2GU 100~2000GU:±0.2%GU		
Chromaticity corresponds	CIE C light source, CIE 1931(2°)Luminosity corresponding		
Measurement Time	1.5s	0.5s	0.5s
Size	6.30x2.95x3.54 inches		
Weight	About 0.77 lbs		
Battery Performance	3200mAh 3.7V Li-ion Battery, 5,000 times within 8 hours		
Display	3.5-inch TFT color LCD, Capacitive Touch Screen		
Interface	USB		
Data Storage	Basic:1000, statistics:5000, continuous:5000		
Software	Quality management software, quality inspection report printing, more function expansion		
Working Temp	0-40°C(32-107°F)		
Humidity	<85%RH, No Condensation		

Standard Accessories	Charger, USB data cable, manual, Quality management software (official website download or after-sales service), calibration standard board
Optional Accessories	Micro Printer

The TT-TRI-GLOSS-III series is an intelligent gloss meter that can be controlled via a touch screen and offers more functions compared to the HG series.



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 

Phone: +971 488 19252
Email: me@torontech.com

