

COULOMETRIC KARL-FISCHER TITRATION TESTER



Coulometric Karl-Fischer Titration Tester TT-6304

Coulometric Karl-Fischer Titration Tester complies with ASTM D4377, ASTM D6304, and ASTM D4928 standards. It is used to test the water content in crude oil, which is crucial for refining, purchasing, selling, or transferring crude oils.


The Coulometric Karl-Fischer Titration Tester TT-6304 measures water content ranging from 0.02% to 2% in crude oils. While mercaptan and sulfide (S- or H_2S) sulfur are known to interfere with this test method and affect the determination of water content in the 0.005% to 0.02% range, the extent of this interference at these levels has not been fully determined. Therefore, for the 0.005% to 0.02% range, no precision or bias statement is available.

APPLICATIONS

The Coulometric Karl-Fischer Titration Tester is used for the precise determination of water content in various substances. Applications include:

- **Petroleum Industry:** Testing the water content in crude oil, which is critical for refining, purchasing, and selling.
- **Pharmaceuticals:** Ensuring quality control by accurately measuring water content.
- **Chemicals:** Used for a wide range of chemical products.
- **Food and Cosmetics:** For quality control and research and development.

The tester can be used for all sample types, including liquids, solids, slurries, and gases, and is particularly effective for samples with low moisture content.



FEATURES

Coulometric Karl-Fischer Titration Tester TT-6304 is controlled by an SCM, featuring system fault self-diagnosis, a color LCD touch screen, and a user-friendly interface. The tester automatically deducts blank current, ensuring high accuracy in test results. It also includes a large current background compensation function, significantly reducing standby time. A unique reagent failure detection function alerts the user to replace expired reagent, maximizing reagent usage. The built-in multiple water content formulas cater to various user needs. The device is equipped with a high-efficiency mini printer and a large-capacity storage system that can hold up to 500 test records. The convenient retrieval mode allows users to easily read and print test reports.

TECHNICAL SPECIFICATIONS

Coulometric Karl Fischer Titrator - TT-6304

Technical Specifications

Parameter	Specification
Measuring Range	3 µg to 150 mg H ₂ O
Resolution	0.1 µg
Accuracy (water content below 10 µg)	±2 µg
Accuracy (water content 10 µg to 500 µg)	±3 µg
Electrolysis Rate	2.0 mg/min maximum
Electrolysis Current	Pulse current, 400 mA

Parameter	Specification
Power Supply	AC 220 V $\pm$ 10%, 50 Hz (110 V version available on request)
Ambient Temperature	0°C to 40°C
Relative Humidity	85% or below, non-condensing



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 🇨🇦

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 🇺🇸

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 🇦🇪

Phone: +971 488 19252
Email: me@torontech.com

