

VOLUMETRIC KARL FISCHER MOISTURE TITRATOR



Volumetric Karl Fischer Moisture Titrator TT-203

Volumetric Karl Fischer Moisture Titrator TT-203 conforms to ASTM E203 Standard Test Method for Water Using Volumetric Karl Fischer Titration.

Volumetric Karl Fischer Moisture Titrator TT-203 is an automatic volumetric Karl Fischer titrator with high accuracy, great flexibility, and repeatability. The titrator is designed to perform titrations for a variety of sample types and matrices, allowing the user to achieve reliable results and high-speed analysis. The TT-203 analyzes water content ranging from 100 ppm to 100%. This advanced titrator automatically dispenses the titrant, detects the endpoint, and performs all necessary calculations and graphing.

APPLICATIONS

The primary application of this titrator is to automatically determine the water content in a wide variety of sample types and matrices, in compliance with the ASTM E203 standard.

It is specifically designed for:

- High-accuracy analysis of water content ranging from 100 ppm to 100%.
- Performing titrations with high speed and repeatability.

FEATURES

- LCD display screen
- Supports KF Titration Mode and Titer Detection Mode
- Features auto-filling, auto-purging, and auto-mixing of the reagents for safe handling of Karl Fischer chemicals

- Selectable units including mg, mg/L, %, ppm, etc.
- Settable parameters, including measurement unit, polarization current, stirring rate, titration rate, stop volume, endpoint potential, stop criterion, etc.
- Stores up to 200 titration data sets (GLP-compliant)
- Data can be easily transferred to a printer via the RS-232 communication interface
- Reset feature automatically returns all settings to factory default options

TECHNICAL SPECIFICATIONS

1. Range: 0.1 mg to 250 mg, 0.1 mg
2. Test Range: 100 ppm to 100%
3. Polarization Current Accuracy: $1\ \mu\text{A} \pm 0.2\ \mu\text{A}$, $50\ \mu\text{A} \pm 10\ \mu\text{A}$
4. Repeatability: $\pm 0.5\%$
5. Power Supply: AC adapter, 100 to 240V AC input, 24V DC output (110V also available)
6. Dimensions: 340 x 400 x 400 mm
7. Weight: 10 kg



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 

Phone: +971 488 19252
Email: me@torontech.com

