



HIGH SPEED HYPERSENSPECTRAL SORTING SYSTEM: FS- 18/19

High Speed Hyperspectral Sorting System: FS-18/19 built for industrial sorting applications.

This advanced line scan camera meets the high-speed scanning demands of industrial use, thanks to its high-frequency capabilities. With a sturdy construction and a compact design, it offers increased flexibility for various installation setups.

High Speed Hyperspectral Sorting System FS-1819

APPLICATIONS

Application fields


High Speed Hyperspectral Sorting System: FS-18/19

FEATURES

- Spectral range: 900-1700nm
- Imaging speed: up to 1480fps
- Spectral resolution: 6nm
- Suitable for all environments
- Supports multiple regional ROIs
- Includes hyperspectral image processing software

TECHNICAL SPECIFICATIONS

Model number	FS-18(Short-wave Infrared SWIR)	FS-19(Short-wave InfraredSWIR)
Lighting mode	Passive lighting (without light source)	
Spectroscopic method	Grating	
Spectral range	900-1700nm	
Spectral band	512	256
Spectral resolution (FWHM)	6nm	
Slit width	25um	
Transmission efficiency	> 60%	
Stray light	< 0.5%	
Number of spatial pixels	640	
Pixel size	5um	15um
Imaging speed	740fps	1480fps
Probe	InGaAs	
SNR(Peak)	600/1	
Camera output	Cameralink	
Camera interface	C-Mount	
Attachment	Lens, USB cable, power supply	
ROI	Individual region	



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 🇨🇦

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 🇺🇸

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 🇦🇪

Phone: +971 488 19252
Email: me@torontech.com

