



XENON ACCELERATED WEATHERING TEST CHAMBER - TORONXTC™-2200H

Xenon Accelerated Weathering Test Chamber - ToronXTC™-2200H is a high-performance xenon aging test chamber designed to simulate the damaging effects of full-spectrum sunlight, high temperatures, and humidity. This chamber can replicate the aging effects of months or even years of outdoor exposure in just a few days or weeks, making it ideal for accelerated testing.

APPLICATIONS

Standards

1. **ASTM G151**: Standard Practice for Exposing Nonmetallic Materials in Accelerated Test Devices That Use Laboratory Light Sources
2. **ASTM G155**: Standard Practice for Operating Xenon Arc Light Apparatus for Exposure of Non-Metallic Materials
3. **ISO 11341**: Paints and Varnishes - Artificial Weathering and Exposure to Artificial Radiation - Exposure to Filtered Xenon-Arc Radiation
4. **ISO 4892**: Plastics - Methods of Exposure to Laboratory Light Sources - Part 2: Xenon-Arc Lamps
5. **SAE J2527**: Performance Standard for Accelerated Irradiation of Automotive Exterior Materials by Xenon Arc Lamp Radiators
6. **SAE J2412**: Accelerated Aging of Automotive Interior Components Using a Controlled Irradiance Xenon Arc Device

Advantages

1. **Powerful Xenon Lamp:** Equipped with a 1.8 KW air-cooled long arc Xenon lamp(Made in US) for reliable and efficient testing.
2. **User-Centric Design:** Optimized for ease of use, offering the best solutions for sample handling and loading.
3. **Comprehensive Testing Capabilities:** Fully functional chambers designed for aging resistance, colorfastness, and lightfastness, adhering to all major industry standards.
4. **Premium Components:** Premium functional parts to ensure top-notch performance and durability.
5. **Cost-Effective:** Delivers high-quality performance with affordable purchase and operating costs.
6. **High-Quality Services:** Offers robust aging test chambers along with professional testing services.
7. **Expert Support:** Backed by an experienced team for installation, maintenance, training, and consulting.
8. **User-Friendly Interface:** Simple, intuitive programming for seamless operation.
9. **Enhanced Safety:** Equipped with over ten protection configurations for greater operational security.
10. **Full-Spectrum Sunlight Simulation:** Accurately reproduces ultraviolet, visible, and infrared light for realistic environmental testing.
11. **Smart Diagnostics:** Includes self-diagnostic alarms and maintenance reminders to ensure smooth and efficient operation.

This test chamber offers a perfect blend of advanced technology, reliability, and cost-efficiency, making it an ideal choice for demanding aging and durability assessments.

FEATURES

- **Xenon Light Source & Filter:** Made in United States, accurately simulates the full spectrum of sunlight for optimal and realistic testing.
- **Uniform Irradiation:** Drum-shaped sample holder rotates automatically, ensuring even energy distribution across all test panels.
- **Automated Energy Control:** Sun Eye Control System provides precise and stable irradiation energy, compensating for variations due to lamp aging. Adjustable range:

- 0.30 W/m²-0.75 W/m² @ 340 nm
 - 0.5 W/m²-1.35 W/m² @ 420 nm
 - 0 W/m²-90 W/m² @ 300-400 nm
- **Long Lamp Life:** Xenon lamp lasts up to 1,500 hours, meeting the highest international standards.
- **Flexible Filters:** Multiple internal and external optical filters available, which can be replaced during testing to maintain light transmittance and meet international test standards.
- **Precise Environmental Control:**
 - Temperature control (black panel, black scale, or inner chamber temperature) with a range from room temperature to 100°C.
 - Irradiance control at 340 nm or 420 nm.
 - Humidity control from 20% to 95%.
- **Customizable Test Programs:**
 - 9 programmable test programs (each with 10 data segments).
 - 6 preset international standard programs.
- **Data Collection & Storage:** Test data automatically recorded in Excel format, exportable via USB for hands-free operation.
- **User-Friendly Touch Screen:** Allows easy parameter setup and real-time monitoring of the test process.
- **Precision Sensors:** High-precision Pt 100 black panel and black scale temperature sensors for accurate temperature control.
- **Alarm Protection:** Alerts for issues such as large irradiance errors, high cooling water temperature, and low water flow.
- **Ease of Use & Low Maintenance:** Simple to use, virtually maintenance-free, and designed for any testing environment.
- **Adjustable Test Plate Frame:** Ensures uniform irradiation and better data consistency across tests.
- **Accelerated Aging:** Exposes samples to sunlight equivalent to peak summer noon hours, 24/7, speeding up the aging process.
- **Cost-Effective:** Low purchase price, affordable lamp costs, and low operating expenses, making the ToronXTC-2200H accessible for even small labs.

TECHNICAL SPECIFICATIONS

Specification	Details	
Xenon lamp	1.8KW air-cooled long arc Xenon lamp(Made in US)	
Filter	Daylight filter (Window glass filter or UV extension filter also available)	
Exposure area	2200 cm²□ 22pcs standard samples of 150mm×70mm can be exposed to the sun at one time)	
Irradiance monitoring point	340nm, 420nm, 300nm~400nm (300nm□ 800nm)	
Automatic irradiation control	(0.30W/m²-0.75W/m²) @340nm (0.5W/m²-1.35W/m²) @420nm (0W/m²-90W/m²)300nm-400nm	
Lamp life approx.	1500 hours	
Temperature range	Black panel	Black label
	RT+30°C□ 100°C	RT+30°C□ 100°C
Cabinet air	RT+10°C□ 65°C	
Humidity range	Light□ 10%-75% spray or dark cycle□ 10%-95%	
Note: The temperature range is slightly different depending on the external environment andtheset irradiance		
Sample Rotating Speed	1r/min□ around the center of the tube□	
Sample Tray Load Capacity	Up to 4.5kg	
Inlet Pressure	2.8-5.5 bar	
Influent Water Purity	Deionized water with conductivity < 0.1 μS and silica content < 0.2ppm	
Water Consumption	1.0 L/min (Spray) 8 L/day (humidified)	

Specification	Details
Humidification gas source	0.3~0.8Mpa
External Dimensions(W×D× H)	865mm×800mm×1780mm
Weight approx.	240kg
Voltage	380V□ 50Hz



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 🇨🇦

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 🇺🇸

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 🇦🇪

Phone: +971 488 19252
Email: me@torontech.com

