



ATMOSPHERE FURNACE TT-AF-64-1400

1400°C chamber atmosphere furnace features a flange-sealed body for reliable operation. During heat treatment, protective gases such as nitrogen, argon, or oxygen can be introduced for processing carbon, metal, and biomass materials. It is also suitable for sintering ternary lithium battery materials.

Model No.	TT-AF-64-1400
Inner Dimension (WxDxH MM)	400x400x400
Continuous Temperature	1300°C
Max Temperature	1400°C
Voltage	380V/18kw
Heating Element	Silicon Carbide Rod (SiC) heater
Temperature Precision	±1°C
Thermocouple	S type

APPLICATIONS

- **Pilot-Scale Production:** Primary application for high-throughput heat treatment, sintering, and annealing in a substantial 400 x 400 x 400mm chamber (64L capacity), ideal for scaling up processes.
- **Advanced Materials Processing:** Optimized for the sintering of ternary lithium battery materials, ceramics, and other industrial components that require stable thermal cycles up to 1300°C continuous operation.
- **Precise Atmosphere Management:** Features a flange-sealed body for reliable processing under controlled atmospheres (N2, Ar, O2) and includes pre-evacuation vacuum capability up to 20,000Pa.

- **Complex Process Control:** Supports advanced, multi-stage processing requirements with a program controller capable of executing up to 30 segments for customized and repeatable thermal curves.
- **Cost-Effective Industrial Option:** Designed for durability and continuous factory-scale production, with chamber options available up to 1000L in the series.

Atmosphere Furnace TT-AF-64-1400

Atmosphere Furnace TT-AF-64-1400

Atmosphere Furnace TT-AF-64-1400

Atmosphere Furnace TT-AF-64-1400

FEATURES

Furnace Shell

- Constructed from Q235 low-carbon steel with an electrostatically resistant, anti-corrosion surface.
- Sturdy tank-style shell design ensures a low external surface temperature.
- Furnace door with flange-sealed structure and manual screw compression; side-opening design for easier operation.

Refractory Material

- Multi-layer insulation system made of lightweight alumina ceramic fiber and other high-quality insulating boards. Asbestos-free, with low heat loss and reduced energy consumption.

Heating System

- Premium heating elements securely mounted on both sides of the furnace, providing free-radiation heating for energy efficiency, high performance, and long service life.
- Dual-side (left and right) heating elements ensure excellent temperature uniformity inside the chamber.

Temperature Control Panel

- PID control with SSR output for precise temperature regulation.
- Equipped with an international-standard thermocouple for durability and accuracy.
- Chamber capacity options up to 1000L, suitable for factory-scale production.

Program Controller

- Advanced controller capable of handling complex process requirements.
- User-friendly operation with flexible programming.
- Supports up to 30 programmable segments for a single curve.
- Over-temperature and fault alarms with automatic safety protection.

Vacuum Atmosphere Function

- Furnace chamber includes adjustable inlet and outlet ports for introducing protective gases.
- High-performance rotary vane vacuum pump capable of achieving a vacuum level of 20,000 Pa.
- Optional gas circuit control unit available, supporting 1-3 adjustable float flow meters.

TECHNICAL SPECIFICATIONS

Product Model	Chamber Size □ mm□	Volume	Max Temp	Work Temp	Voltage	Power	Heating Element	Controller Accuracy
---------------	--------------------	--------	----------	-----------	---------	-------	-----------------	---------------------

TT-AF-8-1200	200×300×120	8L	1200°C	1100°C	220V (110V is also available)	3KW	HRE	±1°C
TT-AF-12-1200	200×300×200	12L	1200°C	1100°C	220V (110V is also available)	4KW	HRE	±1°C
TT-AF-18-1200	250×300×250	18L	1200°C	1100°C	220V (110V is also available)	6KW	HRE	±1°C
TT-AF-30-1200	300×500×200	30L	1200°C	1100°C	380V	7.5KW	HRE	±1°C
TT-AF-8-1400	200×200×200	8L	1400°C	1350°C	220V (110V is also available)	5KW	SIC	±1°C
TT-AF-12-1400	200×300×200	12L	1400°C	1350°C	220V (110V is also available)	5KW	SIC	±1°C
TT-AF-18-1400	250×300×250	18L	1400°C	1350°C	220V (110V is also available)	6KW	SIC	±1°C
TT-AF-36-1400	300×400×300	36L	1400°C	1350°C	380V	12KW	SIC	±1°C
TT-AF-45-1400	300×500×300	45L	1400°C	1350°C	380V	14KW	SIC	±1°C
TT-AF-8-1700	200×200×200	8L	1700°C	1600°C	220V (110V is also available)	5KW	MoSi2	±1°C
TT-AF-12-1700	200×300×200	12L	1700°C	1600°C	220V (110V is also available)	6KW	MoSi2	±1°C
TT-AF-20-1700	250×320×250	20L	1700°C	1600°C	380V	7KW	MoSi2	±1°C
TT-AF-36-1700	300×400×300	36L	1700°C	1600°C	380V	13KW	MoSi2	±1°C



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 🇨🇦

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 🇺🇸

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 🇦🇪

Phone: +971 488 19252
Email: me@torontech.com

